


408,000LBS FORCE DIRECTLY TO STUCK POINT IN 6 1/2" TO 8 1/2" OPEN HOLE

Combination of inflatable open hole anchor with DHPT enables full jacking force downhole directly at stuck point



Features

- Deploy full jacking force close to fish
- Low operational risk
- Anchor in open hole
- Known forces applied directly to fish



TAM 5 1/2" Inflatable Anchor (Other sizes available on request)



Field Proven	Multi-use capability
Simple Operation; <ul style="list-style-type: none"> • Pressure up - Anchor inflates • Bleed off pressure - Anchor deflates 	Rating; <ul style="list-style-type: none"> • Pressure 5,300 psi* • Tensile 434,000 lbs* <p><small>* Maximum operating, safety factor included</small></p>

Typical Applications

Recovery of stuck drilling BHA
Recovery of stuck fishing BHA
Recovery of retrievable OH packers
Fishing liners
Recovery of swell packers
Fishing drill pipe
Recovery of logging BHA's

Benefits

- Reduced wear and tear on BHA, workstring and derrick
- No friction lost at the curve
- Immediate indication when the fish is free
- No excessive overpull at surface
- Reduce drill pipe stretch

Description	DownHole Power Tool (DHPT)	
DHPT OD	4.440 in	5.750 in
Max. Force Generation*	265,000 lbf	498,000 lbf

*At 100% of yield, no safety factor

Learn more about the working loads of the DHPT with TAM Inflatable Anchor

[Click Here to View](#)

